



1 FIRST FLOOR PLAN - PLUMBING  
1/8"=1'-0"

SYMBOL	DESCRIPTION
---	SANITARY WASTE (SW)
- - - -	SANITARY VENT (SV)
---	COLD WATER (CW)
---	HOT WATER (HW)
---	HOT WATER RETURN (HWR)
○	PIPE TURNED DOWN
○	PIPE TURNED UP
●	BALL VALVE
↓	BALANCING VALVE

NUMBER	TYPE OF FIXTURE	DRAINAGE		WATER		REMARKS – REFER TO NOTES BELOW SCHEDULE
		WP	VP	CW	HW	
P-103	VITREOUS CHINA, WALL HUNG WATER CLOSET BATTERY POWERED SENSOR FLUSH VALVE	4"	2"	1 1/4"	---	PROVIDE FOR TOILET ROOMS. ADA ACCESSIBLE, SIPHON JET, BATTERY POWERED, SENSOR OPERATED FLUSHVALVE.
P-201	VITREOUS CHINA, WALL HUNG URINAL BATTERY POWERED SENSOR FLUSH VALVE	2"	2"	3/4"	---	PROVIDE FOR TOILET ROOMS. SIPHON JET, BATTERY POWERED, SENSOR OPERATED, WATER SAVER FLUSHVALVE.
P-202	VITREOUS CHINA, WALL HUNG URINAL BATTERY POWERED SENSOR FLUSH VALVE	2"	2"	3/4"	---	PROVIDE FOR TOILET ROOMS. ADA ACCESSIBLE, SIPHON JET, BATTERY POWERED, SENSOR OPERATED, WATER SAVER FLUSHVALVE.
P-414	VITREOUS CHINA, WALL HUNG LAVATORY GOOSENECK FAUCET	1 1/2"	1 1/2"	1/2"	1/2"	PROVIDE FOR TOILET ROOMS.; ADA ACCESSIBLE WITH MANUAL WRIST BLADE GOOSENECK FAUCET WITH LAMINAR FLOW.
P-417	VITREOUS CHINA, COUNTER TOP GOOSENECK FAUCET	1 1/2"	1 1/2"	1/2"	1/2"	PROVIDE FOR TOILET ROOMS.; ADA ACCESSIBLE WITH MANUAL SINGLE HANDLE GOOSENECK FAUCET WITH LAMINAR FLOW.
P-528	STAINLESS STEEL SINGLE BASIN COUNTERTOP MOUNTED SINK	1 1/2"	2"	3/4"	3/4"	1 COMPARTMENT SINK WITH DECK MOUNTED MANUAL GOOSENECK FAUCET WITH WRIST BLADE HANDLES AND LAMINAR FLOW OUTLET.
P-529	EXISTING STAINLESS STEEL SINGLE BASIN COUNTERTOP MOUNTED SINK	---	---	3/4"	3/4"	REMOVE EXISTING FAUCET AND INSTALL A NEW DECK MOUNTED MANUAL GOOSENECK FAUCET WITH WRIST BLADE HANDLES AND LAMINAR FLOW OUTLET.
P-712	EXISTING SHOWER EXISTING SHOWER VALVE	---	---	3/4"	3/4"	REMOVE EXISTING SHOWER HEAD AND INSTALL A NEW FIXED SHOWER HEAD WITH CHROME PLATED METAL HEAD AND ADJUSTABLE BALL JOINT WITH 2.5 GPM FLOW.

- NOTES:
- WHERE COLOR/FINISH OPTIONS ARE AVAILABLE FOR FIXTURES, SELECTIONS SHALL BE SUBMITTED TO THE ARCHITECT PRIOR TO PURCHASE AND INSTALLATION.
  - VERIFY SINK DIMENSIONS WITH ARCHITECT, RE: MILLWORK.
  - REFER TO ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHTS OF ALL FIXTURES.
  - FIXTURES FOR USE BY THE HANDICAPPED:
    - INSTALL IN ACCORDANCE WITH A.D.A., STATE, AND LOCAL REQUIREMENTS.
    - THE FORCE REQUIRED TO ACTIVATE FLUSH VALVES SHALL BE 5 LBS MAXIMUM.
    - FLUSH ACTIVATOR SHALL BE LOCATED ON WIDE SIDE OF THE STALL.
    - THE FAUCET CONTROLS AND THE OPERATING MECHANISM (OPERABLE WITH ONE HAND) SHALL BE OF THE TYPE NOT REQUIRING AN OPERATING FORCE EXCEEDING 5 LBS, OR TIGHT GRASPING, PINCHING OR TWISTING OF THE WRIST.
  - PROVIDE INSULATED COVERINGS FOR WASTE, TRAP, CW AND HW SUPPLIES ON ADA ACCESSIBLE PLUMBING FIXTURES WHERE OTHER MEANS OF PROTECTION ARE NOT PROVIDED BY ARCHITECT.
  - WHEN REPLACING FAUCETS ON EXISTING SINKS CONTRACTOR SHALL VERIFY EXISTING HOLE PUNCH DIMENSIONS AND COORDINATE NEW FAUCET REQUIREMENTS.

Revisions	No.	Date	Remarks

**Hernandez Consulting**  
ALBERT ARCHITECTURE



**Allen&Hoshall**  
engineering since 1915

Approved:	Title	Signature

Project Title	PLUMBING – FIRST FLOOR PLAN
Approved Service Engineer	
Approved Service Director	

Project Title	Southeast VA Health Care System (SLVHCS) A&E Design Urgent Care
Building Number	
Location	1601 Perdido Street, New Orleans, LA

Date	January 18, 2013
Project No.	VA256-C-0231
DRAWING NO.	P101
Dep.	1 OF 1

